

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Print Date 01.10.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Isopropanol
REACH No. : 01-2119457558-25-XXXX
CAS No : 67-63-0
EU Index No : 603-117-00-0
EC No : 200-661-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Manufacture of substance. Use as an intermediate. Distribution of substance
Formulation and (re)packing of substances and mixtures. Uses in coatings. Uses in
cleaning agents. Use as binders and release agents. Agrochemical uses. Use as a
fuel. Use as a functional fluid. Laboratory agents. Water treatment chemicals. De-
icing and Anti-icing applications. Other consumer uses.

Uses advised against : This product is not recommended for any industrial, professional or consumer uses
other than those identified above.

1.3 Details of the supplier of the safety data sheet

Company : Vet-Way Ltd,
1 Harrier court
Airfield Business Park
Elvington
York
YO41 4EA
UNITED KINGDOM
Telephone : +44 (0)1904 607600
Fax : +44 (0)1904 607601

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Physical hazards

Flam. Liq. 2 - H225

Health Hazards

Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards:

Not classified

Classification System (67/548/EEC or 1999/45EC)

Xi;R36. F;R11, R67

Human health

Irritating to eyes. May cause serious eye damage. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May cause skin sensitisation or allergic reactions in sensitive individuals. In high concentrations, vapours may be irritating to the respiratory system. In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. See Section 11 for additional information on health hazards.

Environmental

Not considered as an environmental hazard according to CLP criteria.

Physicochemical

This product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation

Hazard Pictograms



Signal Word: Danger

Hazard Statements:

- H319 Causes serious eye irritation
- H225 Highly flammable liquid and vapour
- H336 May cause drowsiness or dizziness

Precautionary Statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P233 Keep container tightly closed
- P270 Do not eat, drink or smoke when using this product
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing
- P313 Get medical advice/attention
- P501 Dispose of contents/container in accordance with national regulations

Supplementary precautionary Statements

- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical equipment
- P242 Use only non sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray
- P264 Wash contaminated skin thoroughly after handling
- P271 Use only outdoors or in a well ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/ face protection.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 Call POISON CENTER if you feel unwell.

P337 If eye irritation persists: Get medical attention/advise.

P370 +P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P235 Store in a well -ventilated place. Keep cool.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up

Result of PBT and vPvB assessment

PBT: not applicable

vPvB: not applicable

SECTION 3: Composition/information on ingredients

3.1 Chemical Characterisation: Substances

Identification number(s)

Product name ISOPROPANOL

REACH registration number 01-2119457558-25-XXXX

EU index number 603-117-00-0

CAS no 67-63-0

EC No 200-661-7

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Keep affected person under observation. Effects may be delayed. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

If inhaled

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person under observation. Get medical attention if symptoms are severe or persist. Show this Safety Data Sheet to the medical personnel.

In case of skin contact

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.

In case of eye contact

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

If swallowed

Get medical attention immediately. Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Keep affected person under observation. Show this Safety Data Sheet to the medical personnel.

First aid personnel should wear appropriate protective equipment during any rescue.

4.2 Most important symptoms and effects, both acute and delayed

General information

Get medical attention immediately. The casualty should be transferred to hospital as soon as possible.

Inhalation

Vapours/aerosol spray may irritate the respiratory system. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects. Over exposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

Ingestion

Gastrointestinal symptoms, including upset stomach. Diarrhoea. Nausea, vomiting.

Skin Contact

Prolonged contact may cause redness, irritation and dry skin. Product has a defatting effect on skin.

Eye Contact

Causes serious eye irritation. Immediate first aid is imperative. Vapour or spray in the eyes may cause irritation and smarting.

4.3 Indication of any immediate medical attention and special treatment needed

No specific recommendations

SECTION 5: Firefighting measures

5.1 Extinguishing Media

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Do not use water jet as an extinguisher, as this will spread the fire. Non alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Solvent vapours may form explosive mixtures with air. May ignite at high temperature. Highly flammable liquid and vapour. Vapours may accumulate on the floor in low-lying areas. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours may be ignited by a spark, a hot surface or an ember.

Hazardous combustion products: Oxides of carbon. Acrid fumes or smoke.

5.3 Advice for firefighters

Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents. Use protective equipment appropriate for surrounding materials.

5.4 Further information

no data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Take precautionary measures against static discharges. Take care as floors and other surfaces may become slippery. Follow precautions for safe handling described in this safety data sheet. For personal protection see Section 8.

6.2 Environmental precautions

Environmental manager must be informed of all major spillages. Do not discharge into drains or watercourses or onto the ground. Avoid discharge into the aquatic environment. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3 Methods and materials for containment and cleaning up

Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Avoid the spillage or runoff entering drains, sewers or watercourses. Take care as floors and other surfaces may become slippery. Contain spillage with sand, earth or other suitable non-combustible material. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Dispose of contents/container in accordance with international regulations. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

6.4 Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours and spray/mists. Avoid spilling. Avoid release to the environment. Use explosion-proof electrical, ventilating and lighting equipment. Use only in well-ventilated areas. Use suitable respiratory protection if ventilation is inadequate. Take precautionary measures against static discharge. Earth container and transfer equipment to eliminate sparks for static electricity. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge. AVOID splash filling. Do not use compressed air for filling or discharging operations.

Advice on general occupational hygiene

Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. Contaminated clothing should be placed in a closed container for disposal or decontamination.

7.1 Conditions for safe storage, including any incompatibilities

Storage:

Keep away from oxidizing materials, heat and flames. Store in tightly closed, original container in a well ventilated place. Bund storage facilities to prevent soil and water pollution in the event of spillage. Earth container and transfer equipment to eliminate sparks from static electricity. Storage tanks and other containers may be earthed. Keep away from food, drink and animal feeding stuffs. Only store in correctly labelled containers. Suitable container materials: Carbon steel. Mild steel. Stainless steel. Unsuitable containers: aluminium. May attack some plastics, rubber and coatings.

Further information about storage conditions:

Flammable liquid storage.

Specific end use(s)

The identified uses for this product are detailed in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

ISOPROPANOL

Long-term exposure limit (8-hour TWA): WEL 400ppm 999mg/m³

Short-term exposure limit (15 minute): WEL 500ppm(Sk) 1250mg/m³

Additional information: WEL = Workplace Exposure Limit

ISOPROPANOL (CAS: 67-63-0)

Ingredient comments	WEL = Workplace Exposure Limits
DNEL	Industry - Inhalation; Long term systemic effects: 500mg/m ³ Industry - Dermal; Long term systemic effects: 888mg/kg/day Consumer - Dermal; Long term systemic effects: 319mg/kg/day Consumer - Inhalation; Long term systemic effects: 89mg/m ³ Consumer - Oral; Long term systemic effects 26mg/kg/day
PNEC	Industry - Fresh water; Long term; Long term 0140.9mg/l Industry - Marine water; Long term 140.9mg/l Industry - Sediment (Freshwater); Long term 552mg/kg Industry (Marinewater); Long term 552mg/kg Industry - Soil; Long term 28 mg/kg

Exposure controls

Appropriate engineering controls

As this products contains ingredients with exposure limits, process enclosures, local exhaust ventilation or any other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Ensure the ventilation system is regularly maintained and tested. Use explosion-proof electrical, ventilating and lighting equipment. This product must not be handled in a confined space without adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal protective equipment

Eye/face protection

Wear eye protection. If risk of splashing, wear safety goggles or face shield. Personal protective equipment for eye and face protection should comply with European Standard EN 166(EU).

Skin protection

Wear protective gloves. The selected gloves should have a breakthrough time of at least 8 hours. It is recommended that gloves are made of the following material: Butyl rubber. Polythene. Viton rubber (fluoro rubber). For short-term/splash protection the following are recommended Neoprene. To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer who can provide information about the breakthrough time of the glove material.

Body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

Hygiene measures

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated clothing should be places in a closed container for disposal or decontamination.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Organic vapour filter. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marker. Gas and combination filter cartridges should comply with European Standard

EN14387. Change filter cartridge on respirator daily. Check that the respirator fits tightly and the filter is changed regularly. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. When spraying, wear a suitable supplied-air respirator.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Liquid Colour: colourless
b) Odor	Alcoholic
c) Odor Threshold	no data available
d) pH	no data available
e) Melting point/freezing point	Melting point/range: -89 °C
f) Initial boiling point and boiling range	82 °C @1013hPa
g) Flash point	12°C CC (Closed Cup)
h) Evaporation rate	1.5 BuAc=1
i) Flammability (solid, gas)	
j) Upper/lower flammability or explosive limits	Lower: 2% V Upper: 12% V
k) Vapour pressure	42 hPa @ 20°C 62 hPa @ 25°C
l) Vapour density	2
m) Bulk density	785kg/m ³ at 20 °C
n) Water solubility	soluble in water. Miscible with organic solvents.
Viscosity	1.2mPa s @ 20 °C

9.2 Other safety information

Refractive index 1.377

Molecular weight 60.09

Volatility 100%

Saturation content 105

Volatile organic compound

This product contains a maximum VOC content of 100%

SECTION 10: Stability and reactivity

10.1 Reactivity

May react with Strong acids and Strong oxidizing agents.

10.2 Chemical stability

Stable at normal ambient temperatures and when used as recommended.

10.3 Possibility of hazardous reactions

Reacts with strong acids. Reacts with strong oxidizing agents.

10.4 Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid heat. Avoid contact with the following materials: Strong oxidizing agents and acids.

10.5 Incompatible materials

Strong acids, Strong oxidizing agents

10.6 Hazardous decomposition products

Oxides of carbon. Acrid smoke or fumes

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral - 500mg/kg

Dermal - 1100mg/kg

Inhalation - 11.0(vapours mg/l)

Toxicological information on ingredients

ISOPROPANOL

Acute toxicity - oral	LD50 5045 mg/kg, Oral, Rat.
Acute toxicity - dermal	LD50 12800 mg/kg, Dermal, Rabbit.
Acute toxicity - inhalation	LC50 20 mg/l Inhalation, Rat.
Animal data	Not classified as irritating to the skin
Serious eye damage/irritation	Classified as irritating to eyes
Respiratory sensitisation	Not classified as a respiratory sensitiser
Genotoxicity - in vitro	Does not contain any substances known to be mutagenic
Carcinogenicity	Does not contain any substances known to be carcinogenic
Reproductive toxicity - fertility	Based on available data the classification criteria are not met
Reproductive toxicity - development	This substance has no evidence of toxicity to reproduction
STOT - single exposure	May cause drowsiness or dizziness Target organs - Brain, Central Nervous System
STOT- repeated exposure	Based on available data the classification criteria are not met.
Aspiration hazard	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Vapours/aerosol spray may irritate the respiratory system. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Overexposure may depress the central nervous system, causing dizziness and intoxication. Extensive use of the product in areas with inadequate ventilation may result in accumulation of hazardous vapour concentrations.
Ingestion	Gastrointestinal symptoms, including upset stomach. May cause nausea, headache, dizziness and intoxication. Diarrhoea.

Skin contact	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Product has a defatting effect on the skin. May cause skin sensation or allergic reactions in sensitive individuals.
Eye contact	Causes serious eye irritation. Repeated exposure may cause chronic eye irritation. Risk of serious damage to eyes.
Acute and chronic health hazards	Irritating to eyes.
Route of entry	Inhalation, Ingestion, Skin and/or eye contact.
Target organs	Central nervous system. Eyes, Gastro-intestinal tract, Skin
Medical Symptoms	Drowsiness, dizziness, disorientation, vertigo. Intoxication. Symptoms following over exposure to dust may include the following: Irritability. Headache. Nausea, vomiting. CNS depression. Irritation of eyes and mucous membrane. Confusion, agitation and/or excitation.
Medical Considerations	Central nervous depression. Splash in eye requires examination by eye specialist. Persons with rash are directed to skin expert for examination of allergic eczema.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic Toxicity:

ISOPROPANOL

The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

Acute toxicity - Fish	LC50, 96 hours, 9640 mg/l, Pimephales promelas (Fat-head minnow)
Acute toxicity - Aquatic invertebrates	EC50, 24 hours: >10000 mg/l, Daphnia Magna
Acute toxicity - Aquatic plants	EC50, 96 hours: 1726-2278 mg/l, Scenedesmus subspicatus

12.2 Persistence and degradability

Readily biodegradable. Oxidises rapidly by photochemical reactions in air.

12.3 Bioaccumulative potential

log Pow: - 0..05

Not expected to bioaccumulate significantly.

12.4 Mobility in soil

Isopropanol

The product is water soluble and may spread in water systems. Large volumes may penetrate soil and could contaminate groundwater. If product enters soil it will be mobile and may contaminate ground water.

Surface tension 22.7 mN/m @ 20°C

12.5 Results of PBT and vPvB assessment

Isopropanol does not contain any substances classified as PBT or vPvB according to EU criteria.

12.6 Other adverse effects

Isopropanol contains substance or substances that will contribute to global warming and are not expected to have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Contaminated packages must be completely emptied before sending away for laundering and re-use. When handling waste, the safety precautions applying to handling of the product should be considered.

Contaminated packaging

Collect and place in suitable waste disposal containers and seal securely. Empty containers or liners may retain some product residues and hence be particularly hazardous. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Disposal of this product, process solutions, and residues and by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Confirm disposal procedures with environmental engineer and local regulation. Avoid the spillage or run-off entering drains, sewers or watercourses.

SECTION 14: Transport information

14.1 UN number

1219

14.2 UN proper shipping name

Isopropanol (Isopropyl Alcohol)

14.3 Transport hazard class(es)

3

14.4 Packaging group

II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

EmS F-E, S-D

Emergency Action Code 2YE

Hazard Identification Number 33

Tunnel restriction code (D/E)

14.7

Transporting in bulk according to Annex II of MARPOL73/78 and the IBC code.

Cat Z

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Health and Safety at Work etc. Act 1974 (as amended).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

Dangerous Substances and Explosive Atmospheres Regulations 2002.

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.

Guidance

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

Safety Data Sheets for Substances and Preparations.

Authorisation (Title VII Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2 Chemical Safety Assessment

A chemical safety assessment has been carried out on the components.

SECTION 16: Other information

Further information

Key Literature references and sources for data

Dangerous Properties of Industrial Materials Report, N. Sax et. Al. Registry of Toxic Effects of Chemical

Substances (RTECS). ECHA

Issued by Director - technical and Regulatory Affairs
Revision date 15/09/2014
Revision 3
SDS number 1003
SDS status Approved

Risk phrases in full R11 Highly flammable
R36 Irritating to eyes
R67 Vapours may cause drowsiness or dizziness.

Hazard phrases in full H225 Highly flammable liquid and vapour
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.
